

NASA TECHNICAL
MEMORANDUM

NASA TM X-64607

STRUCTURAL DAMPING IN
SATURN VEHICLES AND SCALE MODELS


By Larry Kiefling and Homer Pack
Aero-Astroynamics Laboratory

July 8, 1971

CASE FILE
COPY

NASA

*George C. Marshall Space Flight Center
Marshall Space Flight Center, Alabama*

1. REPORT NO. NASA TM X-64607		2. GOVERNMENT ACCESSION NO.		3. RECIPIENT'S CATALOG NO.	
4. TITLE AND SUBTITLE STRUCTURAL DAMPING IN SATURN VEHICLES AND SCALE MODELS				5. REPORT DATE JULY 8, 1971	
				6. PERFORMING ORGANIZATION CODE	
7. AUTHOR(S) Larry Kiefling and Homer Pack				8. PERFORMING ORGANIZATION REPORT NO.	
9. PERFORMING ORGANIZATION NAME AND ADDRESS George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35182				10. WORK UNIT NO.	
				11. CONTRACT OR GRANT NO.	
12. SPONSORING AGENCY NAME AND ADDRESS NASA Washington, DC 20546				13. TYPE OF REPORT & PERIOD COVERED TECHNICAL MEMORANDUM	
				14. SPONSORING AGENCY CODE	
15. SUPPLEMENTARY NOTES					
16. ABSTRACT <p>An empirical equation previously used to fit Saturn I dynamic test structural damping data is found to fit Saturn IB and Saturn V bending and torsional modal structural damping data. It is shown that the equation is not applicable to longitudinal mode data or to any data for scale models of the Saturn vehicles.</p> <p>Since the Saturn series consisted of a large variety of configurations and stage sizes, the equation is believed to be usable for the prediction of structural damping of the bending and torsional modes for many future liquid propelled rocket vehicles.</p>					
17. KEY WORDS Damping, structural damping, vibration, energy dissipation, torsional damping, longitudinal damping.			18. DISTRIBUTION STATEMENT Unclassified-Unlimited  E. D. Geissler Director, Aero-Astrodynamics Laboratory		
19. SECURITY CLASSIF. (of this report) UNCLASSIFIED		20. SECURITY CLASSIF. (of this page) UNCLASSIFIED		21. NO. OF PAGES 15	
				22. PRICE \$3.00	

STRUCTURAL DAMPING IN SATURN VEHICLES AND SCALE MODELS

I. INTRODUCTION

Through the years, there has been a continued need for an analytical method of obtaining the damping characteristics of lightly damped structures. Chang [1] was able to derive an empirical equation which successfully described the Saturn I Dynamic Test Vehicle (SAD-6) damping characteristics for lateral bending. He did this by equating the energy dissipated per cycle as a function of the maximum kinetic energy in the structure of the vehicle.

This report is aimed at applying the method of Chang to different space vehicle configurations, and attempts to extend the method to the longitudinal and torsional vibration modes. Since this report involves compilation of previously published test data, no details of the particular test equipment, procedures, data reduction methods, etc., are given. The interested reader can find this information in the referenced material.

II. DAMPING CHARACTERISTICS FOR LATERAL VIBRATIONS

Chang's equation is given as

$$D_C = 0.313 T_0^{0.8} , \quad (1)$$

where D_C represents the energy dissipated per cycle and T_0 the maximum kinetic energy of the structure. The coefficient of T_0 in equation (1) is based on the units of newton-meters for the energy. (Note that the units and coefficient of T_0 are different from those used by Chang.)

Chang's results of the SAD-6 test are shown in figure 1. The number of test points has been reduced by averaging the data for each mode given in figure 1. It is seen that 83 percent of the total data lie within a ± 2 db band. This spread in the dissipated energy seems moderate considering the many parameters which enter into the calculation of T_0 and D_C and the associated measurement errors of these parameters. Since the publication of reference 1, data for a large number of Saturn type vehicles and stages have become available. In figure 2, the empirical equation (1)

was used to fit the damping data for all the vehicle configurations tested. Along with the line representing equation (1), the ± 2 db lines are drawn. It is seen that equation (1) yields a surprisingly good fit over all the vehicle configurations, especially when considering that the energy levels range over seven orders of magnitude, the vehicle masses vary from 33,600 to 721,000 kg, and the frequencies vary from 0.5 to 14.0 Hz. One should also notice that the vehicle configurations tested include not only single but multiple tank structures as well. Therefore, it is believed that equation (1) can be used as a good first approximation for predicting damping characteristics of similar space vehicle configurations for the lateral bending modes.

In stability and response analyses, the damping ratio ζ is the most convenient damping characteristic of a structure. It can be readily obtained from equation (1) as

$$\zeta = \frac{D_C}{4\pi T_O} . \quad (2)$$

Substituting from equation (1) into equation (2) yields

$$\zeta = \frac{.313}{4\pi T_O^{0.2}} . \quad (3)$$

Assuming that equation (1) is a valid representation of the damping characteristics of the investigated structures, it follows from equation (3) that the damping ratio ζ is slightly decreasing with increasing amplitudes of the lateral bending vibration. This is certainly an unusual result, since the damping ratio is usually considered to be independent of the amplitude of the vibration. It is seen from equation (3) that an increase of the amplitude by a factor of two decreases the damping ratio ζ by 32 percent. This fact should be taken into consideration in response analyses in which the amplitudes exceed those of the dynamic test programs. We believe, however, that further research in this area is necessary to obtain a better understanding of the damping mechanism of complex structures.

III. DAMPING CHARACTERISTICS FOR TORSIONAL VIBRATIONS

The damping characteristics for torsional vibration tests are shown in figure 3 for four Saturn V configurations. It was found that the test data can be better fitted by a relationship which is slightly different

from equation (1), which was used for the lateral vibration data. This relationship is given by

$$D_C = 0.34 T_o^{0.80}. \quad (4)$$

This equation indicates that the energy dissipation in the torsional mode is a little higher than that of the bending mode for the same test amplitudes. However, the data show a greater scatter, because only 67 percent of the data (rather than 83 percent for the lateral vibration) fall between the ± 2 db bounds. This greater scatter is likely to be caused by the high concentration of potential energy in the Service Module/Command Module connecting structure. In addition, the energy levels for the torsional modes were generally smaller than those for the lateral modes. The smaller energy levels tend to increase the scatter. Unfortunately, only a limited range of data is available. Because of this high scatter, it is felt that the difference between equation (1) and equation (4) is not statistically significant, and that equation (1) can be used for both the lateral and torsional vibration.

IV. DAMPING CHARACTERISTICS FOR LONGITUDINAL VIBRATIONS

The damping characteristics for the longitudinal vibration tests are shown in figure 4 for two Saturn V configurations. It is seen that the slopes for the energy dissipation vs the energy level of the longitudinal vibration is significantly different for the two configurations tested. Therefore, no unique equation for predicting the damping characteristics of the longitudinal vibration of a structure can be established. However, further research in this area might unveil a missing parameter which could explain the difference in the damping behavior of these configurations.

There is one important difference which should be noticed. The straight lines which were fitted to the longitudinal test data have a slope which is greater than unity. As a consequence, the damping ratio for the longitudinal vibration mode is increasing for increasing amplitude. This result is opposite to the damping behavior of the structure vibrating in its lateral or torsional mode, where it was found that the damping ratio was decreasing with increasing amplitude. At the present time, no conclusive physical explanation can be given for this different behavior.

V. DAMPING CHARACTERISTICS FOR SCALE MODELS

Several attempts have been made in recent years to predict the damping characteristics of a structure from dynamic tests on scale models. Figure 5 is included to show that the Chang equation could not be used for the test data obtained from a 1/5 scale model Saturn I and a 1/10 scale model Saturn V. This would indicate that the damping characteristics cannot be predicted from scale model tests or that the Saturn scale models were deficient in modeling some still unknown parameter.

VI. CONCLUSIONS

1. The structural damping equation established by Chang can be applied to the bending and torsional vibrations of Saturn-type vehicles and similar configurations.
2. The Chang equation or any similar equation cannot be applied to the longitudinal vibrations or to the scale models of the Saturn-type vehicles.
3. The damping ratio ζ depends on the amplitude of the vibration. For the lateral and torsional modes, it decreases with increasing amplitudes.
4. The damping ratio ζ increases with increasing amplitude for the longitudinal modes of Saturn-type vehicles.




Figure 1. Damping in Bending Vibrations of SAD-6 (from reference 1)




Figure 2. Damping in Bending Vibrations of Saturn Vehicles




Figure 3. Damping in Torsional Vibrations of Saturn Vehicles




Figure 4. Damping in Longitudinal Vibrations of Saturn V Vehicles




Figure 5. Damping in Bending Vibrations of Saturn Scale Models

REFERENCES

1. Chang, C. S., "Damping in Multi-Beam Vibration Analysis, Part II," Lockheed HREC Report TM 54/20-12, November 1964.
2. Anon., "Saturn V Dynamic Test Vehicle Configuration I Test Report," Vols. I and II, Boeing Document T5-6630, May 1967.
3. Anon., "Dynamic Test Results of S-IVB-D, I.U., LEM, and Apollo," Chrysler Technical Report HSM-R154, January 1966.
4. Anon., "Dynamic Test Results of SA-202 Upper Stages," Chrysler Technical Report HSM-R162, March 1966.
5. de la Garza, E., "AS-204/LM-1 Static and Dynamic Pull Test Correlation and Revised AS-207 and A S-208 Cantilevered Pad Modes," Chrysler Technical Note TN-AP-67-294, January 16, 1968.
6. Anon., "Saturn V Dynamic Test Vehicle Configuration II Test Report Report Pitch and Yaw Test Results," Vols. I and II, Boeing Document T5-6633-1, September 1967.
7. Anon., "Saturn V Dynamic Test Vehicle Configuration I Test Report Torsional Test Results," Boeing Document T5-6630-3, May 17, 1967.
8. Anon., "Saturn V Dynamic Test Vehicle Configuration II Test Report Torsional Test Results," Boeing Document T5-6633-2, August 31, 1967.
9. Anon., "Saturn V Dynamic Test Report Configuration II C.O. MSFC 201 Test Report Torsional Test Results," Boeing Document T5-6633-5, September 27, 1967.
10. Mixson, John S. and John J. Catherine, "Experimental Lateral Vibration Characteristics of a 1/5-scale Model of Saturn SA-1 with an Eight-Cable Suspension System," NASA TN D-2214, November 1964.
11. Leadbetter, Sumner A., "Some Preliminary Experimentally Determined Frequencies, Mode Shapes, and Damping of a 1/10-Scale Apollo-Saturn V Dynamic Model - Pitch Response," LWP-90, March 8, 1965.
12. Leadbetter, Sumner A. and H. Wayne Leonard, "Some Preliminary Experimentally Determined Frequencies, Mode Shapes, and Damping of a 1/10-Scale Apollo-Saturn V Dynamic Model - Pitched Response, Staged Model," LWP-121, July 12, 1965.
13. Anon., "Saturn V Dynamic Test Vehicle Configuration I Test Report Longitudinal Test Results," Boeing Document T5-6630-4, May 17, 1967.
14. Anon., "Saturn V Dynamic Test Vehicle Configuration II Test Report Longitudinal Test Results, Boeing Document T5-6633-3, Vols. I & II, September 12, 1967.


APPROVAL


STRUCTURAL DAMPING IN SATURN VEHICLES AND SCALE MODELS


by Larry Kiefling and Homer Pack

The information in this report has been reviewed for security classification. Review of any information concerning Department of Defense or Atomic Energy Commission programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

This document has also been reviewed and approved for technical accuracy.


M. H. Rheinfurth
Chief, Dynamics Analysis Branch


J. A. Lovingood
Chief, Dynamics and Control Division


E. D. Geissler
Director, Aero-Astroynamics Laboratory

DISTRIBUTION

DIR
DEP-T
A&TS-PAT
A&TS-MS-H
A&TS-MS-IP
A&TS-MS-IL (8)
A&TS-TU, Mr. Wiggins
PM-PR-M, Mr. Goldston

S&E-DIR

Dr. G. McDonough

S&E-ASTN

Mr. Sterett
Mr. Hunt
Mr. Farrow
Mr. Nichols
Mr. Bullock
Mr. Furman
Mr. Schock

S&E-ASTR

Mr. Wojtalic
Mr. Vallely
Mr. Mink
Mr. Counter

S&E-CSE

Mr. Blackstone

PD

Mr. Denton

S&E-AERO

Dr. Geissler
Mr. Horn
Mr. Lovingood
Mr. Ryan
Mr. Mowery
Mr. Craighead
Mr. Rheinfurth
Mr. Winder
Mr. Worley
Mr. Buchanan
Mr. Muller
Mr. Pack (20)
Mr. Kiefling (20)
Mrs. Hightower

Sci. & Tech. Info. Facility (25)
P. O. Box 33
College Park, Md. 20740
Attn: NASA Rep. (S-AK/RKT)

Mr. Douglas Michael
RV-2
NASA
Washington, DC 20546

Mr. D. Wade
ES-2
NASA, MSC
Houston, Texas 77058

Mr. S. A. Leadbetter
Mail Stop 244
NASA-LRC
Langley Sta.
Hampton, VA 23365

Mr. H. Morgan
Mail Stop 340
NASA-LRC
Langley Sta.
Hampton, VA 23365

Mr. T. G. Butler
Code 321, Rm. 112, Bldg. 7
NASA-GSFC
Greenbelt, MD 20771

Mr. A. L. Erickson
NASA-ARC
Moffett Field, CA 94035

Mr. W. Gayman
Jet Propulsion Laboratory
4800 Oak Grove Dr.
Pasadena, CA 91103

Mr. W. J. Mykytow
Vehicle Dynamics Div.
USAF Flt. Dynamics Lab.
Wright Patterson AFB
Dayton, Ohio 45433

Dr. H. F. Bauer
School of Engineering Science & Mech.
Ga. Inst. of Tech.
Atlanta, GA 30332

Norm Abramson
Southwest Research Inst.
P. O. Drawer 28510
San Antonio, Texas 78228

Mr. L. E. Kraft, SL-24
North American Rockwell Corp.
Space Div.
Seal Beach, CA 90740

Dr. Frank Liu
Univ. of Ala. Huntsville
4701 University Drive NW
Huntsville, AL 35805

Dr. J. T. Oden
Univ. of Ala. Huntsville
4701 University Drive NW
Huntsville, AL 35805

Mr. E. Lerner
Grumman Aerospace Corp.
Structural Mech. - Plant 35
Bethpage, N. Y. 11714

Mr. R. Gieseke
Convair Div., General Dynamics
P. O. Box 1128
San Diego, Calif. 92112

Mr. G. Morosow
Martin Marietta Corp.
Denver Div.
P. O. Box 179
Denver, Col. 80201

Mr. W. D. Whetstone
Lockheed HREC
P. O. Box 1103 West Sta.
Huntsville, AL 35807

Mr. L. Olson
McDonnell-Douglas Corp.
5301 Bolsa Ave.
Huntington Beach, CA 92647

Dr. C. P. Rubin
Hughes Aircraft Co.
Aerospace Group-Space Sys. Div.
Centinela and Teale
Culver City, CA 90230

Dr. R. Mallett
Structural Systems Dept.
Bell Aerosystems Co.
Buffalo, N. Y. 14240

Mr. Grady Riley
The Boeing Co.
P. O. Box 1470
Huntsville, AL 35807

Mr. J. J. O'Conner
Bellcomm, Inc.
955 L'Enfant Plaza North, SW
Washington, DC 20024

Dr. W. A. McNeill
Engineering Div.
Univ. of South Alabama
Mobile, AL 36608

Dr. P. X. Bellini
Civil Engineering Dept.
Youngston State University
Youngstown, Ohio 44503

Mr. J. Wood
Chrysler Corp. Space Div.
P. O. Box 29200
New Orleans, LA 70129

Mr. J. Collins
J. H. Wiggins Co.
P. O. Box 192
Palos Verdes Estates, CA 90274

Mr. D. A. Lee
Mechanics Res. Inc.
9841 Airport Blvd.
Los Angeles, CA 90045

Mr. C. M. Pearson
Northrop Corp.
P. O. Box 1484
Huntsville, AL 35805

Mr. D. H. Mitchel
TRW Systems
1 Space Park
Redondo Beach, CA 90278

Mr. C. S. Chang
Applied Dynamics Res. Corp.
3313 Memorial Parkway SW
Huntsville, AL